

Global SRTM derivatives for hydrological applications at multiple scales

Bernhard Lehner

World Wildlife Fund US

in collaboration with The Nature Conservancy, CIAT, USGS


HydroSHEDS

Hydrological data and maps based on Shuttle Elevation Derivatives at multiple Scales

Project goal: Derive large-scale digital river network and basin maps as key input layers for watershed analyses and hydrological applications


Existing products like the globe resolution) or regional maps ar or their seamless extent


SRTM provides for the first tim DEM at near-global extent, from can be derived



"Useful" resolutions:

- ~ 500 m for large basins and continents
- ~ 1 km for the globe
- Option 1: First upscale SRTM elevation data, then derive flow directions
 - © fast and easy
 - ⊗ low quality
- Option 2: First derive flow network at high resolution, then upscale this network
 - maximum information is preserved
 - ® deriving flow network at 90 m resolution is very laborious
- HydroSHEDS applies option 2, adding the advantage that it
 also provides results at 90 m resolution (while still focusing on
 large scale products)







Main processing steps

- SRTM data preparation
- Void filling
- Sink identification
- Hydrologic conditioning
- Upscaling

SRTM data preparation




Void filling




Sink identification

- Manual inspection
- GIS assisted



Hydrological conditioning


- Lower all voids (JPL or USGS) and water bodies (NGA) (to force the flow into these potential open water surfaces)
- Filter the surface through directional 3x3 neighborhood analysis (to further remove spikes and wells)
- Carve valleys as identified through neighborhood terrain analysis (to remove small obstacles in valleys)
- Weed potential mangrove zones within coastal buffer zone (to avoid backwater effect)
- Burn rivers (ESRI 1:3 Mio.) & lakes (GLWD) into elevation surface (to emphasize most important lakes and river courses)
- Identify draft main river courses, cut through all "humps" along these rivers, and repeat all calculations (to remove dam/bridge/gorge effect)
- Introduce manual corrections (correct obvious errors, burn selected rivers from DCW 1:1 Mio.) and repeat calculations




Upscaling

- Identify all large river courses (> 100 km²) at 90 m resolution
- Burn these rivers into hydrologically conditioned elevation data
- Upscale these elevation surfaces
- Calculate drainage direction map

Quality comparisons



Quality comparisons





Quality comparisons


- Improvement over Hydro1k
- Improvement over ESRI 1:3 Mio. rivers (because they are used in river burning)
- Comparison with DCW 1:1 Mio. depends on location, but mostly improvement
- Less accuracy than local river networks derived from high quality maps or remote sensing – But: HydroSHEDS is seamless and provides full topology information
- HydroSHEDS can be improved through incorporation of local scale information (e.g. high quality vectorized river maps)

Main problems

- Vegetation (particularly in flat areas like large river floodplains)
- Rivers of about 90 m width with high riparian vegetation
- Roads in lowland vegetation (e.g. Amazon basin)
- Areas with low relief
- Braided rivers
- Sinks
- Coastal areas (mangroves, deltas)







HydroSHEDS

Hydrological data and maps Probabandres Sthituths Elevation Deginative as anyltiple as thes)

Derived products include:

1 km (seamless global)

watershed boundaries

Free distribution online via USGS seamless server


flow directions

flow distances

Timeline: Timeline:

South America: available

anned: estimates of flow bal coverage: end 2005 uantities



Thanks

to all collaborators, data providers, the SC Johnson Fund, & the makers of SRTM

You will soon find more information at

www.worldwildlife.org/ science/freshwater.cfm